



HELI-LIFTABLE TANK



HELI-LIFTABLE TANKS

CANFLEX Heli-Liftable tanks can be transported by helicopter, boat or truck to remote locations.

Fast Response tanks that take just minutes to set up with limited personnel.

Easy Storage and Transportation since these units collapse vertically when empty to a fraction of their filled size.

Stability is provided by the conical design even if filled on uneven surfaces. Certified lifting straps are integral to the tank leading to a single lifting point.

Superior Design and Robust Materials allow the "HLC" to be used repeatedly, whether it be remote transport of fluids, hoist maintenance or hoist training.

Complete and Ready to Use, each tank comes with useful accessories: Fill / Offloading connections, vent connection with spark arrestor (fuel transport) or an automatic relief valve (hoist / water weight applications) and its appropriated harness. Fittings are all appropriate for either potable water or hydrocarbons.

TECHNICAL SPECIFICATIONS

Body Material: 49 oz to 77 oz /yd² Urethane

Material Fuel Compatibility: Diesel, JP Fuel, MOGAS, AVGAS, Kerosene, Lube Oils

Flanges w/ M camlock & cap: 1" or 2" Aluminum w/ SS bolts

Capacities: 200 to 2,000 liters (55 to 530 U.S. gal)

INCLUDED ACCESSORIES

- Ball valves with camlocks
- 90 deg elbow with camlocks
- Spark Arrestor-Vent (Hydrocarbons) or Relief valve (Water)
- Tool box: Repair Kit (Optional) and Operator Manual
- Safety Bolt Type Anchor shackle
- Shipping & Storage: Carry Bag made of 18oz PVC

COMMON APPLICATIONS

- Fuel or Water (Fresh or Potable) Transport
- Helicopter hoist testing, maintenance or training
- Remote Location Collection
- Spill Response
- Fire Fighting Efforts
- Transport and storage of essential fluids to populations effected by tsunamis, earthquakes, etc.

TOP FEATURES

- Fuel or Water (Fresh/Potable) Transport
- Helicopter hoist testing/maintenance or training
- Remote Location Collection
- Spill Response
- Fire Fighting Efforts
- Transport and storage of essential fluids to populations effected by tsunamis, earthquakes, etc.



CANFLEX HELI-LIFTABLE TANKS

MODEL	CAPACITY	DIAMETER	FILLED HEIGHT	FILLED WEIGHT	EMPTY HEIGHT	EMPTY WEIGHT
	M ³ / LITERS	M	M	KG	CM	KG
	USG	IN	IN	LBS	IN	LBS
HL-500	1.89 / 18,90	1.4	2.8	1,966	24	77
	500	55.5	113	4,335	9.5	170
HL-300	1.13 / 1,134	1.4	2.1	1,184	20	48
	300	55.5	83	2,610	7.9	105
HL-100	0.37 / 378	0.78	2.2	420	20	41
	100	30	87	926	7.9	90
HL-50	0.18 / 189	0.78	1.3	234	18	34
	50	30	51	515	7	75