



## FOAM FILLED BOOM - 21

### Contractor Boom

The foam filled boom is a versatile, economical, general purpose boom designed for use in many different spill response applications. The boom incorporates cylindrical foam floatation (solid buoyancy) that is cost effective and offers high performance, reliability, and durability.



## TOP FEATURES

- Available in a wide range of heavy-duty PVC coated fabrics
- PVC coated galvanized steel aircraft cable top tension member
- Custom sizes available
- Floats are secured internally which eliminates pinch points or external seals and ensures a smooth external profile for superior oil containment
- Cylindrical foam floatation (rolled polyethylene) for maximum memory characteristics. Will retain shape, will not crush or break into pieces
- Economy model available with polystyrene floatation
- Corrosion resistant ASTM style marine grade aluminum connectors
- Heavy duty galvanized steel ballast chain

## FOAM FILLED BOOM - 21

<b>Boom Height</b>	21 in	533 mm
<b>Float Diameter</b>	8 in	230
<b>Skirt</b>	12 in	305 mm
<b>Standard Length</b>	50 ft	15.25 m
<b>End Connectors</b>	ASTM-Universal LD extruded aluminum	
<b>Skirt Material</b>	PVC-coated polyester	
<b>Skirt Weight</b>	22 oz/yd <sup>2</sup>	750 g/m <sup>2</sup>
<b>Color</b>	Orange	
<b>Flotation Material/Shape</b>	Solid, closed cell polyethylene foam logs	
<b>Fold Points</b>	Every 5 feet	Every 1.52 m
<b>Boom Weight</b>	2 lbs/ft	3 kg/m
<b>Ballast</b>	1/4 in (7.1 mm) Grade 30 galvanized chain	
<b>Ballast Weight</b>	0.73 lbs/ft	1.1 kg/m
<b>Top Tension</b>	Heavy duty, 9400 lb polyester webbing, 1 inch	
<b>Chain Pocket</b>	Fully enclosed in pocket with drain holes	
<b>Mid Anchor Point</b>	5/16" (8 mm) galvanized shackle	