



Offshore/Open Ocean



All seams radio-frequency (RF) welded
Inflatable buoyancy chamber, full length



INFLATABLE BOOM MP 52

Air Filled Boom

Inflatable Boom MP (multi point), is a pressure inflatable boom which uses air for buoyancy. Each Inflatable Boom MP section length (typically 25 m) is segmented into individual inflatable chambers by way of internal bulkheads. This ensures that the boom will maintain positive buoyancy and continue to float in the event of any damage. Booms feature simple, rapid inflation, and high buoyancy to weight ratios for use in waves and demanding conditions.

Booms can be inflated using handheld or backpack inflation blowers, or with integrated hydraulic blowers mounted on a boom storage and deployment reel.

- Most rapid boom deployment, fully automatic. Just pull into the water for immediate containment of spills
- Available in a wide range of heavy-duty PVC and PU coated fabrics
- No moving springs or parts that can rust or fail to operate
- Boom hoops are field replaceable in the event of damage
- Internal bulkheads ensure boom will not sink in the event of puncture
- Corrosion resistant ASTM style marine grade aluminum connectors
- Heavy duty galvanized steel ballast chain
- Custom sizes available
- Compact storage ratios (10:1) in specially designed storage and deployment containers or carry bag

INFLATABLE BOOM MP 52

	Imperial	Metric
Boom Height (Deflated)	52 in	1320 mm
Air Chamber Diameter	18 in	457 mm
Draft	24 in	610 mm
Standard Length	82 ft	25 m
Fabric Weight	23 oz/yd ²	785 g/m ²
Fabric	PVC coated Polyester	
Color	Orange standard, others available	
Internal Air Chamber Length	16.4 ft	5 m
Separation of Chambers	Internal bulkheads, smooth exterior profile	
Inflation Valve	Monsoon Inflation/ Deflation in each chamber	
Pressure Relief	Leaffield A6 valve in each chamber	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Toggle Pins	3/8" (10 mm) stainless steel, spring loaded with lanyard	
Boom Weight	2.9 lb/ft	4.3 kg/m
Ballast	Grade 30, hot dipped galvanized steel chain	
Ballast Size	3/8 in	10 mm
Ballast Weight	1.21 lbs/ft	1.8 kg/m
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m