



LIFEBOAT TEST WATER BAGS

Lifeboat test water bags are used for evenly distributed load tests. These test water bags feature an automatic relief valve which is activated once the lifeboat bags achieve the desired weight.

Capacities: 100, 250, 375, 400, 500 and 1000 kg



Accessories / Parts Included

- *1" NPT flange connection
- 3/4" Threaded Plug with lanyard Drain/ Vent
- Relief Valve
- 1" Ball Valve w/ female camlock

**2" Also available*

Optional Accessories

- 20 ft x 1" suction hose with camlocks
- Port Drain Manifold with camlocks (4 or 6 ports)
- 50 ft x 2" discharge fire hose
- Water meter (gallons or m3)
- Air driven double diaphragm pump
- 6 ft x 2" suction hose with camlocks
- Clip-Lok wood shipping box
- Complete Fill/Offload LBB kit

LIFEBOAT TEST WATER BAGS

Model	Weight	Volume	Diameter	Length	Dry Weight
	kg	Liters / m ³	m	m	kg
	lb	USG	in	in	lb
LBB-100	100	100 / 0.10	0.32	1.50	7
	221	26.4	12.5	59	15
LBB-250	250	250 / 0.25	0.51	1.60	9
	551	66.1	20.0	63	20
LBB-375	375	375 / 0.375	0.51	2.26	10
	826	99.2	20.0	89	22
LBB-400	400	400 / 0.40	0.51	2.40	11
	881	106	20.0	94.5	25
LBB-500	500	500 / 0.50	0.51	2.9	13
	1,102	132	20.0	114	28
LBB-1000	1000	1000 / 0.50	0.64	3.7	34
	2,204	264	25.0	145	75

Notes:

Custom sizes also available.