



## MODULAR FRAME (FAST) TANK

**Versatile and Economical** modular design of the tank allows for one set of sturdy frames to be used for varied size tanks. A wide range of government approved material coated liners are available. The Frame Tank's stable design allows it to be used on virtually any landscape; all that is needed are liners of the desired capacity.

**Quick and Easy Assembly** of the foldable tanks and durable (6061-T6) aluminum structure with liner provide convenient transport, set up and storage. Effective application for firefighting, spill recovery, rapid emergency response and disaster relief efforts.

**Diverse Storage Capability** for bulk liquids: Potable (drinking) Water, Fuels / Hydrocarbons, Waste Products and other essential fluids for populations effected by natural disasters.

## TECHNICAL SPECIFICATIONS

**Body Material:** 27 oz/yd<sup>2</sup> PVC (2 m<sup>3</sup> to 10 m<sup>3</sup>)

**Body Material:** 48 oz/yd<sup>2</sup> PVC (10m<sup>3</sup> to 200 m<sup>3</sup>)

**Flanges / connections:** 2", 3" Aluminum w/ SS bolts

**Capacities:** 500 to 52,000 US gal (2 to 200 m<sup>3</sup>)

## INCLUDED ACCESSORIES

**Ball valves:** 2" and 3" with camlocks

**Ground Sheet:** Prevents abrasions and punctures

**Tool box:** Repair Kit and Operating Manual

**Carry/Storage Bag:** 2 m<sup>3</sup> to 8 m<sup>3</sup>

**Shipping/Storage:** Clip-Lok plywood box 10 m<sup>3</sup> & 200 m<sup>3</sup>

## OPTIONAL ACCESSORIES

**Replaceable Inner Liner:** 15 mil for Hydrocarbons or PW

**Loose Fitted Conical Top:** Available up to CF-FT-12CM

**Aluminum Shipping /Storage:** With lift straps and shackles

**Hose Saddle:** For 2" to 3" suction or drain hose

## CANFLEX COLLAPSIBLE MODULAR FRAME (FAST) TANKS

MODEL	CAPACITY		MAX. DIAMETER	HEIGHT	# OF SIDES (FRAME SETS)	DRY WEIGHT WITHOUT ACCESSORIES		FILL/OFFLOAD CONNECTIONS
	M <sup>3</sup> / BARRELS		M	M		KG		
	USG		FT	FT		LBS		
CF/FT-2CM	2.0 / 12.6		1.95	1.2	5	82	1 X 2 IN NPT	
	530		6.5	3.9		180		
CF/FT-3CM	3.0 / 18.9		2.3	1.2	6	86	1 X 2 IN NPT	
	800		7.5	3.9		190		
CF/FT-4CM	4.0 / 25.1		2.61	1.2	7	96	1 X 2 IN NPT	
	1,000		8.6	3.9		210		
CF/FT-6CM	6.0 / 37.7		3	1.2	8	127	1 X 2 IN NPT	
	1,500		10	3.9		280		
CF/FT-8CM	8.0 / 50.3		3.38	1.2	9	163	1 X 2 IN NPT	
	2,100		11.1	3.9		360		
CF/FT-10CM-E	10.0 / 62.9		3.81	1.2	10	195	1 X 2 IN NPT	
	2,650		12.5	3.9		430		
CF/FT-10CM	10.0 / 62.9		3.81	1.2	10	195	1 X 3 IN NPT	
	2,650		12.5	3.9		430		
CF/FT-12CM	13.2 / 83		4.2	1.2	11	206	1 X 3 IN NPT	
	3,500		13.8	3.9		455		
CF/FT-15CM	15.0 / 94.3		4.5	1.2	12	218	1 X 3 IN NPT	
	4,000		15	3.9		480		
CF/FT-20CM	20.0 / 125.8		5.3	1.2	14	255	1 X 3 IN NPT	
	5,300		17.5	3.9		560		
CF/FT-25CM	25.0 / 157.2		5.65	1.2	15	270	1 X 3 IN NPT	
	6,600		18.5	3.9		600		
CF/FT-30CM	30 / 188.7		6	1.2	16	290	2 X 3 IN NPT	
	8,000		20	3.9		640		
CF/FT-38CM	38 / 239		6.78	1.2	18	306	2 X 3 IN NPT	
	10,000		22.2	3.9		675		
CF/FT-50CM	50 / 314.5		8.3	1.2	22	400	2 X 3 IN NPT	
	13,200		27.1	3.9		880		
CF/FT-80CM	80 / 503.2		10	1.2	26	485	2 X 3 IN NPT	
	21,000		32.2	3.9		1,070		
CF/FT-100CM	100 / 629		11	1.2	29	567	3 X 3 IN NPT	
	26,500		36	3.9		1,250		
CF/FT-150CM	150 / 943.5		13.6	1.2	36	825	3 X 3 IN NPT	
	40,000		44.6	3.9		1,820		
CF/FT-200CM	200 / 1258		15	1.2	40	950	3 X 3 IN NPT	
	52,000		49.5	3.9		2,100		

## CANFLEX COLLAPSIBLE LOW PROFILE MODULAR FRAME (FAST) TANKS

MODEL	CAPACITY	LENGTH	WIDTH	HEIGHT	DRY WEIGHT WITHOUT ACCESSORIES	# FRAME SETS / CONFIGURATION
	M <sup>3</sup> / BARRELS	M	M	CM	KG	
	USG	FT	FT	IN	LBS	
LP/FT-2CM	2.0 / 12.6	2.37	1.18	73.6	52	6 / (2X1)
	530	7.77	3.89	29	115	
LP/FT-4CM	3.8 / 23.8	2.37	2.37	73.6	77	8 / (2X2)
	1000	7.77	7.77	29	170	
LP/FT-6CM	5.7 / 35.7	3.55	2.37	73.6	118	10 / (3X2)
	1,500	11.66	7.77	29	260	
LP/FT-8CM	7.5 / 47.6	4.74	2.37	73.6	134	12 / (4X2)
	2,000	15.54	7.77	29	295	
LP/FT-8CM-S	7.5 / 47.6	3.55	3.55	73.6	134	12 / (3X3)
	2,000	11.66	11.66	29	295	
LP/FT-11CM	11.3 / 71.4	4.74	3.55	73.6	159	14 / (4X3)
	3,000	15.54	11.66	29	350	
LP/FT-15CM	15.0 / 95.2	5.92	3.55	73.6	181	16 / (5X3)
	4,000	19.43	11.66	29	400	
LP/FT-15CM-S	15.0 / 95.2	4.74	4.74	73.6	181	16 / (4X4)
	4,000	15.54	15.54	29	400	
LP/FT-20CM	19.0 / 119	5.92	4.74	73.6	193	18 / (5X4)
	5,000	19.43	15.54	29	425	

**NOTE:** All LP/FT Low Profile Frame Tanks come with 2"X3" NPT connections.