

<b>PRODUCT</b>							
<b>FEATURES</b>	<b>Sea Slug -Towable Bladder "FCB"</b>	<b>Pillow Shaped Tank "CPT"</b>	<b>Pillow Shaped Tank "CPT"</b>	<b>Rectangular Shaped Tank "CRT"</b>	<b>Rectangular Shaped Tank "CRT"</b>	<b>Modular Frame Tank "CF/FT"</b>	<b>Heli- Lifiable Tank "HLC"</b>

**General Material Specifications**

<b>Environment</b>	<b>SEA</b> Ocean, River, Lakes	<b>SEA</b> Transport with vessel	<b>LAND</b>	<b>LAND</b> Transport by truck <b>AIR</b> Transport by plane	<b>LAND</b> Transport by container (QUAD - ISO 20ft & 40ft)	<b>LAND</b>	<b>AIR</b>
<b>Fluids</b>	Hydrocarbons / Spills / Water	Hydrocarbons / Spills / Water / Chemicals	Hydrocarbons / Spills / Water / Chemicals	Hydrocarbons / Spills / Water / Chemicals	Hydrocarbons / Spills / Water / Chemicals	Hydrocarbons / Spills / Water	Hydrocarbons / Water
<b>Solids</b>	No	No	No	No	No	Yes	No
<b>Material (Bladder Body)</b>	PVC or Urethane	PVC or Urethane	PVC or Urethane	PVC or Urethane	PVC or Urethane	PVC or Urethane	PVC or Urethane
<b>Material weight</b>	1622 g/m2 to 3,024 g/m2 (48 oz/y2 to 89 oz/y2)	950 g/m2 to 1622 g/m2 (28 oz/y2 to 48 oz/y2)	950 g/m2 to 1622 g/m2 (28 oz/y2 to 48 oz/y2)	950 g/m2 to 1622 g/m2 (28 oz/y2 to 48 oz/y2)	950 g/m2 to 1622 g/m2 (28 oz/y2 to 48 oz/y2)	950 g/m2 to 1622 g/m2 (28 oz/y2 to 48 oz/y2)	1360 g/m2 to 2685 g/m2 (40 oz/y2 to 79 oz/y2)
<b>Construction Method</b>	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)	Radio Frequency (High Frequency)
<b>Fittings</b>	Anodized Aluminum	Anodized Aluminum	Anodized Aluminum & PVC	Anodized Aluminum & PVC	Anodized Aluminum & PVC	Anodized Aluminum	Anodized Aluminum & PVC
<b>Fittings - available sizes</b>	2", 3", 4" & 6" NPT Pump Hatch 16" & 25"	2", 3", 4" NPT Man Inspection Hole 10"x16"	2", 3", 4" NPT Man Inspection Hole 10"x16"	2", 3", 4" NPT	2", 3", 4" NPT	2", 3", 4" NPT	2" & 3" NPT
<b>Metallic Structure</b>	Marine Grade Anodized Aluminum 6061-T6	n/a	n/a	n/a	n/a	Marine Grade Anodized Aluminum 6061-T6	n/a
<b>Type of Connections</b>	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)	Aluminum Camlocks Male & Female (STA-LOK II or pin w/lanyard)
<b>Valves (ball or butterfly)</b>	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water	PVC for Hydrocarbons or Potable Water

**Body**

<b>Body Shape</b>	Cylindrical main body and matching Conical ends	Pillow shaped	Pillow shaped	Rectangular shape	Rectangular shape	Polygonal circular shape with modular interchangeable sides	Conical shape
<b>Volume</b>	5m3 a 250m3 (1,320 a 66,000 US Gal)	1m3 a 20m3 (264 a 5,300 US Gal)	1m3 a 500m3 (264 a 132,000 US Gal)	1m3 a 14.4m3 (264 a 3800 US Gal)	1m3 a 14.4m3 (264 a 3800 US Gal)	2m3 a 190m3 (530 a 50,000 US Gal)	0.2m3 a 2m3 (55 a 530 US Gal)

**Certifications**

<b>Quality Control &amp; Manufacturing System</b>	ISO 9001:2015	ISO 9001:2015	ISO 9001:2015	ISO 9001:2015	ISO 9001:2015	ISO 9001:2015	ISO 9001:2015 and ABS Weight & Volume
<b>Material PVC or Urethane</b>	Norm DIN & ASTM	Norm DIN & ASTM	Norm DIN & ASTM	Norm DIN & ASTM	Norm DIN & ASTM	Norm DIN & ASTM	Norm DIN & ASTM
<b>Material Type - PVC or Urethane</b>	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61	Hydrocarbons: MIL-T-52983; MIL-PRF-32233(B) Potable Water: NSF/ANSI Standard 61
<b>Camlocks</b>	MIL-C-27487 & A-A-59326	MIL-C-27487 & A-A-59327	MIL-C-27487 & A-A-59327	MIL-C-27487 & A-A-59327	MIL-C-27487 & A-A-59327	MIL-C-27487 & A-A-59328	MIL-C-27487 & A-A-59329; Petroleum Handling

**Norms and Body Integrity**

<b>Bladder Body - Pressure Test</b>	ASTM F1599-95	ASTM F1599-95	ASTM F1599-95	ASTM F1599-95	ASTM F1599-95	n/a	ASTM F1599-95
<b>Material Peel Test</b>	Yes	Yes	Yes	Yes	Yes	Yes	Yes
<b>PVC and/or Urethane Tensile Strength "Peel Test" before construction</b>	ASTM E-4 +1%	ASTM E-4 +1%	ASTM E-4 +1%	ASTM E-4 +1%	ASTM E-4 +1%	ASTM E-4 +1%	ASTM E-4 +1%
<b>PVC and/or Urethane Tensile Strength Calculations before construction</b>	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)
<b>Metallic Structure before manufacturing</b>	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	n/a	n/a	n/a	n/a	Finite Element Analysis (FEA) (ANSYS and/or NASTRAN)	n/a
<b>Webbing harness</b>	FED-STD-191 Breaking Strength Test	FED-STD-191 Breaking Strength Test	FED-STD-191 Breaking Strength Test	FED-STD-191 Breaking Strength Test	FED-STD-191 Breaking Strength Test	n/a	FED-STD-191 Breaking Strength Test