



Canflex (USA), Inc.

Your best choice for flexible containment!

PRESSURE INFLATABLE BOOM

All seams radio-frequency (RF) welded
Inflatable buoyancy chamber, full length

AirBoom SCS 8/16 - Up to offshore/open ocean

AirBoom SCS (single chamber, solid floatation), is a pressure inflatable boom which uses air for buoyancy. Each AirBoom SCS section length (typically 25 m) consists of a single air inflated chamber which has internal foam to offer the performance characteristics of an inflatable boom with the reliability of a foam filled boom. Our most popular inflatable boom design.

Booms can be inflated using handheld or backpack inflation blowers, or with integrated hydraulic blowers (stand alone or mounted on a boom storage and deployment reel.)



Top Features

- Available in a wide range of heavy-duty PVC and urethane coated fabrics
- Single chamber design for rapid boom deployment and internal foam floatation for maximum reliability
- High flow check valves for rapid inflation and deflation
- Ultra compact storage on boom reels or storage pallets
- Corrosion resistant ASTM style marine grade aluminum connectors
- Heavy duty galvanized steel ballast chain

Technical Information

Specification	Imperial	Metric
Boom Height	24 in	1067 mm
Air Chamber Diameter	8 in	457 mm
Skirt Depth	16 in	610 mm
Standard Length	82 ft	25 m
Fabric Weight	22 oz/yd ²	
Fabric	PVC coated Polyester	
Color	Orange standard, others available	
Boom Weight	1.7 lbs./ft	4.0 kg/m
Buoyancy/Weight Ratio	14:1	
Floatation	Low pressure air inflated chamber	
Secondary Floatation	Internal closed cell PE foam for positive buoyancy at all times	
Separation of Chambers	Single Chamber	
Inflation Valve	Monsun XII Inflation (2 per boom)	
Pressure Relief	Leaffield A6 valve (1 per boom)	
End Connectors	ASTM F962-99 extruded marine grade aluminum connector	
Connector Attachment	Boltless, even stress distribution	
Toggle Pins	3/8" (9.5 mm) stainless steel, spring loaded with lanyard	
Ballast	Grade 30, hot dipped galvanized steel chain	
Ballast Size	5/16 in	8.3 mm
Ballast Weight	.83 lbs/ft	1.8 kg/m
Chain Pocket	Fully enclosed, single layer	
Drain Holes	every 10 feet	every 3 m