

# canflex (USA), Inc.

## LIFEBOAT WATER TEST BAGS "LBB"

#### Capacities 100 kg to 1,000 kg

**Technical Specifications** 

Body Material: 36 oz/yd2 PVC (100 kg to 400 kg)

Body Material: 48 oz/yd2 PVC (500 kg to 1000 kg)

Flanges/connections: 1 x 1" NPT Brass w/ SS washer

One 3/4" coin valve and cap with lanyard (Air release)

One 3.25 PSI relief valve (Air and Fluid release)

500 WLL handles with 2" webbing welded along the sides

**Included Accessories** 

1" PVC CAP for 1" NPT Fitting

1" Ball valve with Female Camlock (per bag to work w/ KIT)

Toolbox: Repair Kit and Operator Manual
Optional & Recommended Accessories

Lifeboat FILL / OFFLOAD Kit

Carry / Storage Bag made of 18 oz PVC

Repair Kit with Heat Gun





Lifeboat and Davit Test Water Bags are used for evenly distributed load tests. These load test bags come with fill/offload fittings and an automatic relief valve which is activated once the lifeboat bags achieve the desired weight.

Canflex lifeboat test bags allow for gradual application and uniform distribution of the load. Controlled loading, unloading and minimal handling of the test load to achieve a wide range of capacities results in minimum downtime of equipment during load tests.

- Foldable for easy storage and transportation
- Made of high strength coated fabrics
- Complete Lifeboat Testing System Kit available
- ABS load certificate / verification of capacity available
- ISO 9001:2015 Quality Management Standard
- Lifeboat load testing
- Life Raft load testing
- Gangway load testing
- Free Fall Lifeboat testing
- Davit Launch Life Raft testing
- Platform & Dock testing











### CANFLEX LIFEBOAT TEST WATER BAGS

MODEL		Weight	Volume	Diameter	Length	Dry Weight
		kg	liters / m³	m	m	kg
		lb	USG	in	in	lb
*	LBB-100	100	100 / 0.10	0.32	1.5	7
		221	26.4	12.5	59	15
*	LBB-250	250	250 / 0.25	0.51	1.6	9
		551	66.1	20.0	63	20
*	LBB-375	375	375 / 0.375	0.51	2.26	10

MATERIAL SPECIFICATIONS: High Tenacity PVC coated Polyester Fabric with RF (HF) Welded seams \*Material Weight 36 oz/yd² (1217 g/m²) \*\*Material Weight 48 oz/yd² (1622 g/m²) FITTINGS:

All fittings are marine grade resistant. Each fitting is mounted on a patch that has a diameter greater than the fitting outside diameter.


Each LBB has one 1" NPT flanged connection w/ PVC cap (Filling / Offloading), located on the top body of the LBB

One 3/4" threaded plug with lanyard (Drain / Vent) located on the top body of the LBB

One relief valve (Automatic Pressure Relief) located in one side of the LBB

OPTIONAL: 2" NPT fittings and ball valves

OPTIONAL: Gangway Load Test Water Bags with Flat Bottom (Models LBB/FB-250, LBB/FB-375 & LBB/FB-400)







## canflex (USA), Inc.

### LIFEBOAT BAGS "FILLING & OFFLOADING KIT"





**CANFLEX** offers all the required accessories for the filling and offloading of any number of Lifeboat Bags (LBB). The **Filling & Offloading Kit** is shipped and stored in a collapsible and stackable bulk crate made of HDPE plastic. Corners interlock for quick set up and added stability and there is 4-way forklift access. The collapsible bulk container (CBC) complies with ISPM 15 standards for International exports

- 1) 6 x 1" 20ft suction hoses w/ male camlocks at both ends
- 2) 6 x 1" PVC ball valve w/ female camlocks at both ends for manifold
- 3) 1 x 6 port manifold w/ 2" M camlock w/ ball valve x F camlock w/ dust cap
- 4) 1 x 2" 50ft fill/discharge fire hose w/ 2-1/2 NST swivel x 2" female camlock. Fire hose can be converted from fire 2-1/2 NST thread to a 2" male camlock connection.
- 5) 1 x water meter w/ female camlock w/ ball valve x female camlock
- 6) 1 x Air driven double Diaphragm water pump w/ female camlocks
- 7) 1 x 2" 6 ft suction hose w/ male camlocks at both ends
- 8) Shipping/Storage HDPE collapsible crate (CBC2: 48x45x50"H)

























