



Canflex (USA), Inc.

Your best choice for flexible containment!

FOAM FILLED BOOMS

**All seams radio-frequency (RF) welded
Stainless steel hardware / fasteners**

Contractor Boom 6/12 - Port, Harbours, Inland waters with low currents and wave action

The foam filled boom is a versatile, economical, general purpose boom designed for use in many different spill response applications. The boom incorporates cylindrical foam floatation (solid buoyancy) that is cost effective and offers high performance, reliability, and durability.



CONTRACTORBOOM 6/12

Top Features

- Available in a wide range of heavy-duty PVC coated fabrics
- Custom sizes available
- Floats are secured internally which eliminates pinch points or external seals and ensures a smooth external profile for superior oil containment
- Cylindrical foam flotation (rolled polyethylene) for maximum memory characteristics. Will retain shape, will not crush or break into pieces
- Economy model available with polystyrene flotation
- Corrosion resistant ASTM style marine grade aluminum connectors
- Heavy duty galvanized steel ballast chain

Technical Information

Specification	Imperial	Metric
Boom Height	19 in	483 mm
Floats	6 in dia.	152 mm dia.
Skirt	12 in deep	305 mm deep
Standard Length	50 ft	15.2 m
End Connectors	ASTM-Universal LD extruded aluminum	
Skirt Material	PVC-coated polyester	
Skirt Weight	22 oz/yd ²	750 g/m ²
Color	Orange	
Fabric Strip Tensile Strength	400 lbs/in	141 kg/2cm
Flotation Material/ Shape	Solid, polyethylene foam logs	
Top Tension Member	1/4" PVC-coated galvanized aircraft cable	
Boom Weight	1.8 lbs/ft	2.7 kg/m
Ballast	1/4 in (7.1 mm) Grade 30 galvanized chain	
Ballast Weight	0.73 lbs/ft	1.1 kg/m
Chain Pocket	Single layer	
Anchor Point	5/16" (8 mm) galvanized anchor shackle	