



Canflex (USA), Inc.

Your best choice for flexible containment!

FOAM FILLED BOOM

All seams radio-frequency (RF) welded
Stainless steel hardware / fasteners

FenceBoom 24 - Sheltered/calm waters, low current

FenceBoom is a solid buoyancy, fence-type boom for spill containment and recovery operation in relatively calm waters. FenceBoom is one of the most economically priced booms available while still providing excellent performance and durability.

FenceBoom offers the smallest storage volume of foam filled boom types, and can be stored on pallets, in containers, or on BoomReels.



FENCEBOOM 24

Top Features

- Available in a wide range of heavy-duty PVC coated fabrics
- Custom sizes available
- Available with optional additional vertical stiffeners and top tension members for increased performance in rougher conditions
- Economy model available with polystyrene floatation
- Corrosion resistant ASTM style marine grade aluminum connectors. Shotgun (H) connectors also available.
- Heavy duty galvanized steel ballast chain

Technical Information

Specification	Imperial	Metric
Boom Height	24 in	610 mm
Freeboard	6.6 in	168 mm
Draft	17.4 in	508 mm
Standard Length	50 ft	15.25 m
End Connectors	ASTM-standard extruded aluminum connectors	
Skirt Material	PVC-coated polyester	
Skirt Weight	22 oz/yd ²	750 g/m ²
Color	Orange standard, others available	
Flotation Material / Shape	Rectangular closed cell, flexible, oil resistant polyethylene foam	
Flotation Size	2 in thick x 5 in tall	50 mm thick x 127 mm tall
Boom Weight	1.7 lbs/ft	2.5 kg/m
Buoyancy	3.9 lbs/ft	5.8 kg/m
Buoyancy/Weight Ratio	2.3:1	
Ballast/Tension Member	5/16 in (8.3 mm)	
Ballast Weight	.83 lbs/ft	1.2 kg/m
Chain Pocket	Single layer, fully enclosed	
Drain Holes	In chain pocket, every 3 m (10 ft)	

All above values are nominal and subject to change without notice.