



# Canflex (USA), Inc.

Your best choice for flexible containment!

## SEA BOOM OCB-2200

Heavy Duty Inflatable Oil Containment Boom

### Deep Sea/Offshore

Canflex Sea Boom OCB-2200 is designed for oil spill operations in the deep sea and offshore areas. Sea Booms feature simple, rapid inflation, and high buoyancy to weight ratios giving them excellent wave conformance in demanding conditions. Each section of the oil curtain boom is segmented into individual inflatable chambers ensuring that the boom will maintain positive buoyancy and continue to float in the event of any damage.

The Sea Boom is made from heavy duty PU-coated polyester fabric. It is both strong and lightweight. This durable polyurethane material has exceptional tensile strength, high abrasion resistance and tear resistance. Its smooth surface resists oil, chemicals, and marine growth, in addition to withstanding severe weather and UV light. All seams and unions are high frequency welded, maintaining the excellent mechanical properties of the fabric, and ensuring air and water tightness.



- Simple to clean
- 2 year warranty
- Repels marine growth
- Open or Enclosed Chain options

**SEA BOOM OCB-2200**

### Top Features

- Rapid inflation and deflation
- Low maintenance and easy to clean
- Handles on each section for easy pick up
- Excellent wave conformance and oil retention characteristics
- Independent, segmented buoyancy chambers
- Corrosion resistant ASTM style marine grade aluminum connectors
- Heavy duty galvanized steel ballast chain
- Marine grade shipping / storage crate (Optional)

### Technical Information

Height (deflated)	87 in	2.2 m
Freeboard	33 in	0.83 m
Draft	37 in	0.94 m
Section lengths	164ft/ 328ft/ 656ft	50m/100m/200m
Ballast galvanized chain	1/2"	12.7 mm
Chamber length	177 in	4.5 m
End connector	ASTM or Pin	
Weight with chain	11.4 lb/ft	17.0 kg/m
Material weight	77 oz/yd <sup>2</sup>	Urethane- 2,618 g/m <sup>2</sup>
Tensile Strength	1300 lbs	5,380 N
High temperature Heat resistance	+160 deg F	+80 deg C
Low temperature- Cold track	-51 deg F	-60 deg C
Color	Black or orange	
Recommended application	Deep Sea/Offshore	